



Mobile DC Charging

Mobile 10kW CHAdeMO, CCS 2.

10KW MOBILE CHADEMO OR CCS2.
COMMERCIAL PRIVATE AND CAR RENTAL APPLICATIONS.

- Ultra compact DC charger.
- Compatible with CHAdeMO or CCS Combo charging sockets.
- Native OCPP client server.
- RFID card, credit card payment system supported.
- 7" touch display.

Technical features

GENERAL PRESENTATION		CONNECTIVITY AND HMI	
ENCLOSURE	Steel with anti-corrosion treatment	DISPLAY	Touch display + Emergency Stop
DIMENSIONS (H x D x W)	300 x 240 x 120 mm	USER INTERFACE	RGB LED band
COLOUR	RAL on demand	COMMUNICATION PROTOCOL	OCPP 1.5 and OCPP 1.6
WEIGHT	20 kg	COMMUNICATION	3G, LAN
IP INDEX	IP 54	RFID	-ISO14443A/B/B' -(Mifare, Calypso, Desfire, NFC reader mode) -Other features on demand
SHOCK RESISTANCE INDEX	IK 10		
TEMPERATURE	From -25 °C to 50°C		
HUMIDITY INDEX	20% - 95%		
COOLING	Fan cooling		

SETTINGS AND POWER SUPPLY		
INPUT	VOLTAGE	380VAC ± 5% 3-phase
	FREQUENCY	45/55Hz± 1%
	CURRENT THD	< 5%
	PROTECTION	-Integrated MCB and RDC 30mA -Surge protector device (option)
OUTPUT	CHARGE POINTS	1 single car use
	CONNECTORS	CHAdeMO / Tesla (need adapter) / CCS 2
	VOLTAGE	0-450VDC , 0-750VDC
	CURRENT	20Amax
	POWER	10kW
	EFFICIENCY	97% three phase
	POWER FACTOR	>0.99 at >50% load

- IEC 61851-1
- IEC 61851-21
- IEC 61851-22
- IEC 61851-23
- IEC 61851-24
- IEC 62196
- IEC 62052
- IEC 62053




Certifications



10 kW DC mobile charging station

- ▶ THREE PHASE DC CHARGER.
- ▶ OUTPUT 10KW.
- ▶ CHADEMO & CCS2.
- ▶ EMERGENCY STOP BUTTON.



CHAdeMO

CCS Type2