



Mobile DC Charging

**Mobile 7kW to 60kW
CHAdeMO, CCS 2.**

7-12KW 15-25K 30-45KW AND 60KW CHADEMO OR CCS2 MOBILE USE.
COMMERCIAL PRIVATE AND CAR RENTAL APPLICATIONS.

- Wheel based.
- Compatible with CHAdeMO or CCS Combo charging sockets.
- Native OCPP client server.
- RFID card, credit card payment system supported.
- 3.2 LCD touch display.

Technical features

GENERAL PRESENTATION		CONNECTIVITY AND HMI	
ENCLOSURE	Steel with anti-corrosion treatment	DISPLAY	3.2 LCED touch display + Emergency Stop
DIMENSIONS (H x D x W)	500 x 480 x 240 mm	USER INTERFACE	RGB LED band
COLOUR	RAL on demand	COMMUNICATION PROTOCOL	OCPP 1.5 and OCPP 1.6
WEIGHT	34 kg	COMMUNICATION	3G, LAN
IP INDEX	IP 23	RFID	-ISO14443A/B/B' -(Mifare, Calypso, Desfire , NFC reader mode) -Other features on demand
SHOCK RESISTANCE INDEX	IK 10		
TEMPERATURE	From -60 °C to 45°C		
HUMIDITY INDEX	5 95%		
COOLING	Fan cooling		

SETTINGS AND POWER SUPPLY		
INPUT	VOLTAGE	400VAC ± 10% 3-phase
	FREQUENCY	50/60Hz± 1%
	POWER FACTOR	>0.99 at >50% load
	PROTECTION	-Integrated MCB and RDC 30mA -Surge protector device (option)
OUTPUT	CHARGE POINTS	1 charging point
	CONNECTORS	CHAdeMO / Tesla (need adapter) / CCS 2
	VOLTAGE	200-500VDC , 250-750VDC
	CURRENT	39.6kW 99Amax@400VDC
	POWER	40kW
	EFFICIENCY	97% three phase



30-45 kW DC charging station

- ▶ THREE PHASE DC CHARGER.
- ▶ OUTPUT FROM 7KW TO 60KW.
- ▶ CHADEMO & CCS2.
- ▶ EMERGENCY STOP BUTTON.
- ▶ RFID PAYMENT SYSTEM.
- ▶ INTERNET CONNECTED SUPPORT.
- ▶ OCPP 1.6 SERVER MANAGEMENT PLATFORM.



Micro 7-12kW



15-25kW



Micro 7-12kW



CHAdeMO

CCS Type2

Compliances

- NFC 15 100
- EN 61000-6
- EN 61000-3

