



Wallmount 7kW Smart LAN multi-norm

Flexible Wallmount IEC and UL Type 1 and Type 2

AC COMPACT WALLMOUNT MULTI NORM IEC AND UL CERTIFIED
DESIGNED FOR RESIDENTIAL OR COMMERCIAL INDOOR & OUTDOOR

- 32Amp 7.3kW single phase
- Compatible with Type 1 J1772 and Type 2 Mennekes
- Native OCPP client server (optional)
- RFID card LAN and Wi Fi supported
- Stylish ergonomic and customizable design

Technical features

GENERAL PRESENTATION		CONNECTIVITY AND HMI	
ENCLOSURE	Polycarbonate	DISPLAY	5 inch LCD
DIMENSIONS (H x D x W)	120x290x410	USER INTERFACE	Remote connection (option)
COLOUR	RAL on demand	COMMUNICATION PROTOCOL	OCPP 1.5 and OCPP 1.6
WEIGHT	7kg	COMMUNICATION	LAN
IP INDEX	IP 55	RFID	-ISO14443A/B/B' -(Mifare, Calypso, Desfire , NFC reader mode) -Other features on demand
SHOCK RESISTANCE INDEX	IK 08		
TEMPERATURE	From -30 °C to 50°C		
HUMIDITY INDEX	5 - 95%		
COOLING	Natural cooling		

SETTINGS AND POWER SUPPLY		
INPUT	VOLTAGE	230VAC 1-phase L/N/PE 208-240VAC 1-phase L1/L2/GND
	FREQUENCY	50/60Hz ± 1%
	CURRENT	32A
	PROTECTION	-Integrated RDC 30mA type A (optional type B) -OVP -OCP -OPP -OTP -UVP -LVP -Surge protector device
OUTPUT	CHARGE POINTS	1
	CONNECTORS	Type 1 J1772 Type 2 Mennekes
	VOLTAGE	208-240VAC
	CURRENT	32A
	POWER	7.3kW (230AC)
	EFFICIENCY	95% at nominal power
	NOISE	-

- IEC 61851-1
- IEC 61851-21
- IEC 62196-2
- UL2594
- UL2231



Certifications



Smart LAN Wallmount T2 or T1 IEC and UL



Configuration options

- RFID
- LAN
- WI FI
- IEC & UL