



Public & Residential 2x 3-44kW AC

Public & Residential up to 2 x 44kW AC SAE J1772 Type 1 & IEC 62196 Type 2

UP TO 88KW T1 OR T2 HOME OR PUBLIC USE CHARGER.
AUTO CONFIGURABLE SINGLE TO THREE PHASE AND 3KW TO 44KW.

- Wall mount or pole standing.
- 1 or 2 car charging.
- Native OCPP client server.
- RFID card, credit card payment system supported.
- 4.3 inch touching display screen panel.

Technical features


GENERAL PRESENTATION		CONNECTIVITY AND HMI	
ENCLOSURE	Steel with anti-corrosion treatment	DISPLAY	4.3" display + Emergency Stop
DIMENSIONS (H x D x W)	500 x 350 x 250 mm	USER INTERFACE	RGB LED band
COLOUR	RAL on demand	COMMUNICATION PROTOCOL	OCPP 1.5 and OCPP 1.6
WEIGHT	18 kg	COMMUNICATION	3G, LAN
IP INDEX	IP 54	RFID	-ISO14443A/B/B' -(Mifare, Calypso, Desfire, NFC reader mode) -Other features on demand
SHOCK RESISTANCE INDEX	IK 10		
TEMPERATURE	From -60 °C to 45°C		
HUMIDITY INDEX	5 - 95%		
COOLING	Natural cooling		

SETTINGS AND POWER SUPPLY		
INPUT	VOLTAGE	1ph 90-250 / 2ph 200-240 / 3ph 208-350Vac ± 5%
	FREQUENCY	50/60Hz± 1%
	POWER FACTOR	>0.99 at >50% load
	PROTECTION	-Integrated MCB and RDC 30mA -Surge protector device (option)
OUTPUT	CHARGE POINTS	1 or 2 charging point
	CONNECTORS	T1 or T2
	VOLTAGE	220 - 380 Vac
	CURRENT	16, 32, 64 Amax
	POWER	Up to 88kW
	EFFICIENCY	99% three phase



1x or 2x 3 kW - 1x or 2x 44 kW
AC charging station

Configuration options



- ▶ SINGLE & THREE PHASE AC CHARGER.
- ▶ OUTPUT FROM 3KW AC TO 44KW.
- ▶ T1 OR T2.
- ▶ EMERGENCY STOP BUTTON.
- ▶ RFID PAYMENT SYSTEM.
- ▶ INTERNET CONNECTED SUPPORT.
- ▶ OCPP 1.6 SERVER MANAGEMENT PLATFORM.

Compliances

- IEC 61851 - 1
- IEC 61851 - 22
- IEC 61851 - 21

